

PVC Fittings



Union



Socket



Elbow


Features

Fittings	Connection Size	Connection Type
Union	1½" & 2" One/both side Female threaded/ Plain	<ul style="list-style-type: none"> • Both End: BSP/NPT Female Threaded • Both End: Plain (Solvent Cement Joint)
Socket	1½", 2", 2½" & 3" One/both side Female threaded/Plain	<ul style="list-style-type: none"> • Both End: BSP/NPT Female Threaded • One End: BSP/NPT Female Threaded Another End: Plain (Solvent Cement Joint) • Both End: Plain (Solvent Cement Joint)
Elbow	1½" & 2" One/Both side Female Threaded / Plain	<ul style="list-style-type: none"> • Both End: BSP/NPT Female Threaded • Both End: Plain (Solvent Cement Joint)

• The Threads follow BSP & NPT standard whereas Plain connection follow ISO/ASTM/DIN/BS etc.
 • The material made of good quality PVC with impact & UV resistant.
 • Max. Operating Pressure: PN-10

Dimensions

Nom Size	BSP Thd./in	NPT Thd./in	ASTM d	BS d	DIN d	ISO d	L1	L2	D1	D2	Lt
40mm (1½")	11	11.5	48.26	48	50	50	37.8	24.6	58	64.8	63
50mm (2")	11	11.5	60.33	60	63	63	35.8	43.6	72.8	85	80
65mm (2½")	11	8	73.03	75	75	75	36.5	49	101.3	101.50	101.3
80mm (3")	11	8	88.9	89	90	90	36.5	49	101.3	101.50	101.3




PVC Union (Both Side - Threaded Female)

PVC Ball Valve ((Inlet - Solvent Joint Female : Outlet - Solvent Joint Female)


Dimensions

Nom Size	BSP Thd./in	NPT Thd./in	ASTM d	BS d	DIN d	ISO d	Lt	D	D1	D2	dm
40mm (1½")	11	11.5	48.26	48	50	50	85.2	94.5	57	60.6	40
50mm (2")	11	11.5	60.33	60	63	63	94.5	116	75.6	73	48



Dimensions

Nom Size	BSP Thd./in	NPT Thd./in	ASTM d	BS d	DIN d	ISO d	L	D
40mm (1½")	11	11.5	48.26	48	50	50	86	59
50mm (2")	11	11.5	60.33	60	63	63	107	72



E-mail: contactus@automatworld.com
 Website: www.automatworld.com

Creating a Green World