

Slip-On Flanges



Features

- Material: Glass Reinforced PP/ Reinforced Nylon/ PVC
- Threaded Socket:
- PPGF Flange Socket: 2" , 2½" & 3" BSP/NPT Female threaded
- Universal Flange Nylon/PVC Socket: 3" & 4" BSP/ NPT Female threaded
- Plain/ Solvent Welded PVC Socket connection: Available as per requirement of ASTM / BS / DIN /ISO standard
- Chemical Resistant: Good resistance to strong acids except highly active oxidizers, such as nitric acid.
- It also has excellent resistance to weak and strong alkalies and to most organic solvents.
- Color: Nylon: Black, PVC: Grey

		Dimensions (in)			Nylon/PVC Slip-on Univ. Flange	
		Glass Reinforced PP Slip-on Flange			3"	4"
Model		2"	2½"	3"	3"	4"
Nominal Dia (mm)	DN	50	65	80	80	100
Max. Operating Pressure (bar)	PN	6	6	6	10	10
Overall Dia (mm)	A	152	165	184	200	225
Bolt circle Dia (mm)	B1	114	126.5	146	145.5	177
Bolt circle Dia (mm)	B2				160	191
Threaded Socket Outside Dia (mm)	C	66.5	90	99	104	130
Flange Thickness (mm)	D	17.5	17.5	17.5	24.5	25.5
Overall Thickness (mm)	E	39.5	39.5	39.5	62	62
Dia. of Bolt (mm)		16	16	16	16	16
No. of Bolt		4	8	8	8	8
Flange Dimensions Suited to Standards		BS10 (Table D & E)			Bs10 (Table D & E), ANSI Class 125/150, ISO 7001 (DIN), BS EN 1092	

