# Aquaturf

### **Impact Pop-up Sprinklers**



#### **Features**

- Interchangeable, bayonet color coded nozzles.
- No tools required to change nozzle.
- Heavy- duty plastic case with reinforced ribbed design for excellent gripping.
- Adjustable to full-circle or part circle.
- Diffuser screw for fine droplets & throw control.
- Double-weighted arm for balance and smooth rotation.
- No back splash during sprinkler running.
- Sand resistant pressure activated wiper seal.
- High Impact strength of pop-up top.
- Excellent distribution unformity.

## **Application**

• Pop-up sprinkler for underground installation in landscaping, residential park, public lawn irrgation.

Performance Table								
Nozzle (mm)	Pressure		Coverage Diameter		Discharge Rate			
	kg/cm²	Psi	mtr.	ft.	LPM	GPM		
2.9 Orange	2	28.4	22.5	74	7.6	29		
	2.5	35.6	23.5	77	8.5	32		
	3	42.7	23.8	78	9.3	35		
	3.5	49.8	24	79	10.1	38		
	4	56.9	24.5	80	10.8	41		
3.2 Green	2	28.4	22.8	75	9.4	36		
	2.5	35.6	23.8	78	10.6	40		
	3	42.7	24.5	80	11.7	44		
	3.5	49.8	25	82	12.6	48		
	4	56.9	25.2	83	13.4	51		
3.5 Blue	2	28.4	23	75	11.3	43		
	2.5	35.6	24	79	12.7	48		
	3	42.7	24.8	81.3	14.1	53.3		
	3.5	49.8	25.3	83	15.1	57		
	4	56.9	25.5	84	16.3	62		
4.0 Black	2	28.4	23.2	76	14.4	55		
	2.5	35.6	24	79	16	61		
	3	42.7	25	82	17.4	66		
	3.5	49.8	25.5	84	18.8	71		
	4	56.9	25.5	84	19.9	75		

<sup>\*</sup>Performance is based on ideal conditions of Temperature, wind velocity and Humidity.

Spacing (m)	CU	DU	SC(5%)	APR
10.0 x 10.0	92	89	1.1	7.6
11.0 x 11.0	89	83	1.3	6.3
10.0 x 12.0	90	86	1.2	6.4
12.0 x 12.0	90	84	1.5	5.3

<sup>\*</sup>Version with Check Valve is also available

# **Technical Specifications**

Discharge: 456-1192 L/HDiameter: 22.5 -25.5 mtr

• Operating pressure: 2.0-4.0 kg/cm<sup>2</sup>

 $\bullet$  Bottom Inlet connection ½" & ¾" female threaded

 $\bullet$  Nozzles available in sizes 2.9, 3.2, 3.5 & 4.0 mm


• Trajectory Angle: 25 degree

• Arc Adjustment range 15 - 345 degree

• Spacing between sprinkler: upto 12m for excellent uniformity.

• Pop up with optional check valve also available.

Nozzle: 3.5mm Pressure: 2.5 kg/cm<sup>2</sup>







E-mail: contactus@automatworld.com Website: www.automatworld.com

