

HT-45G

2" Water Gun DUPLEX



Features

- Available in 2" BSP/NPT Female Thread Connection
- Both Part Circle & Full Circle adjustments
- Only full circle model also available
- Adjustable Jet breaker to provide uniform distribution
- Equipped with interchangeable nozzles of different sizes for various applications

Applications : • Sports Fields, Golf Courses

- Dust Suppression, Green Pastures

Performance Data

Nozzle (mm)	Pressure (kg/cm ²)	Radius (mtr)	Discharge (ltr/min)	Irrigated Area (mtr ²)	Precipitation Rate (mm/h)
12x8	1.5	20	159	1256	7.5
	2.0	23	184	1662	6.6
	3.0	27	224	2289	5.8
	4.0	30	259	2826	5.4
14x8	2.0	25	230	1960	7.0
	3.0	29	280	2640	6.3
	4.0	32	225	3217	6.0
	5.0	34	364	3629	6.0
⚡ 16x8	2.0	27	282	2289	7.3
	3.0	31	344	3017	6.8
	4.0	34	399	3629	6.5
	5.0	37	446	4298	6.2
18x8	2.0	28	343	2461	8.3
	3.0	33	434	3419	7.6
	4.0	36	506	4069	7.4
	5.0	40	561	5024	6.7
20x6	2.0	29	411	2640	9.3
	3.0	34	520	3629	8.5
	4.0	38	606	4534	8.0
	5.0	43	657	5805	6.7

* Performance is based on ideal conditions of Temperature, Wind Velocity and Humidity.
 ⚡ Standard Nozzle Size



Manufactured as per ISO-7749-1&2 specifications



E-mail: contactus@automatworld.com
 Website: www.automatworld.com

Creating a Green World