


Aquamic Inverted

AQ - 210 (Mist Sprayer)



Black Mist Swivel

Features & Specifications

- Operating Pressure Range : 1½ to 2½ kg/cm²
- Fine drops creates uniform cloud.
- Recommended Spacing : 1.0 to 1.5 mtr.
- Coverage Diameter : 2.2 to 4.8 mtr.
- Discharge Flow Rates : 29 to 182 LPH

Applications

- Nurseries, Greenhouses & shade nets.
- Creation of micro climatic condition & humidity control

Performance Chart

Nozzle Color	Size (mm)	Pressure kg/cm ²	Flow (LPH)	Dia. (m)
Black	0.8mm	1.5	29	2.2
		2.0	34	2.4
		2.5	38	2.6
Purple	1.0mm	1.5	45	2.4
		2.0	52	2.6
		2.5	58	2.8
Orange	1.2mm	1.5	66	3
		2.0	76	3.2
		2.5	85	3.4
Blue	1.4mm	1.5	88	3.2
		2.0	102	3.4
		2.5	114	3.6
Yellow	1.6mm	1.5	113	3.8
		2.0	130	4.2
		2.5	145	4.4
Green	1.8mm	1.5	140	4.2
		2.0	162	4.6
		2.5	182	4.8

* Tested at 2m height above ground.

