

Mini T Type Disc Filters

1½" & 2"



AQ-133TR



AQ-134TMR

Specifications	AQ-133TR		AQ-134TMR	
	US Standard	Metric Standard	US Standard	Metric Standard
Inlet/outlet connection	1½" NPT male thread	1½" BSP male thread	2" NPT male thread	2" BSP male thread
Max. Working Pressure (PPGF Filter)	110 Psi	6 kg/cm ²	85 Psi	6 kg/cm ²
Range of Flow Rate	44-88 GPM	12-16 m ³ /h	44-88 GPM	10-20 m ³ /h
Nominal Flow Rate	66 GPM	15 m ³ /h	66 GPM	15 m ³ /h
Filtration Surface area	63.4 in ²	409 cm ²	63.4 in ²	409 cm ²
Material of Construction	Glass Filled Polypropylene		Glass Filled Polypropylene	
Screen Material	Polypropylene Disc	Polypropylene Disc	Polypropylene Disc	Polypropylene Disc
Cartridge Diameter (With O-ring)	2.81 in	71.5 mm	2.81 in	71.5 mm
Cartridge Length	10.2 in	258 mm	10.2 in	258 mm
Available Mesh	120 mesh	120 mesh	120 mesh	120 mesh

Filtering Element

120 Mesh



Head Loss : AQ -133TR & AQ-134TMR					
Flow, m ³ /h	8	10	15	20	24
Pressure Loss, kg/cm ²	0.05	0.09	0.24	0.45	0.76
Flow, GPM	35.2	44	66	88	105.6
Pressure Loss, Psi	0.71	1.28	3.41	6.39	10.79



E-mail: contactus@automatworld.com
 Website: www.automatworld.com

Creating a Green World