

# T-Bolt Hose Clamp/ Layflat Hose Clamp

2", 3", 4", 6", 8", 10" & 12"



## Features

- Solid Stainless steel band.
- Clamp have rolled edge and smooth undersid to prevent hose damage.
- The high strength bolt, designed for this clamp together with captive nut and spacer system.
- For Heavy duty industrial fittings, all parts used of stainless steel grade SS-316.
- The clamp provides the 360degree uniform sealing.
- Bolt & Screw head ensures super strong fit when tightening.
- One bolt which pulls the two halves of the clamp together, creating a strong reliable hose clamp.
- All parts are Stainless steel with an extra strong construction to deliver high strength.
- Ideal for heavy duty applications where large tightening forces are required.
- This is the clamp of choice for professionals in industrial, automotive and agricultural sector where an reliable heavy duty clamp is required.

## Available In

Size	Model No
2"	AQ -352
3"	AQ -354
4"	AQ -355
6"	AQ -356
8"	AQ -357
10"	AQ -358
12"	AQ -359

## Applications

- Heavy duty full stainless steel T-bolt clamps provide uniform sealing pressure for a positive, reliable seal.
- Specifically designed for use in high vibration and large diameter applications.

## Technical Specifications

Diameter (first stage)	2"	3"	4"	6"	8"	10"	12"
Material	SS-304/SS-316	SS-304/SS-316	SS-304/SS-316	SS-304/SS-316	SS-304/SS-316	SS-304/SS-316	SS-304/SS-316
Circumference (mm)	52-58	74-80	98-104	150-168	199-211	242-262	303-323
Width (mm)	22	24	24	26	26	26	26
Wall thickness (mm)	0.8	0.8	0.8	1.0	1.0	1.0	1.0
Screw Length (mm)	70	70	70	120	120	120	120
Head of Screw	hexagonal	hexagonal	hexagonal	hexagonal	hexagonal	hexagonal	hexagonal