

# MARINER

HT- 47G (2½" Water Gun)



- ### Features
- Available in 2½" BSP/NPT Female Thread Connection.
  - Both Part Circle & Full Circle adjustments.
  - Adjustable Jet breaker to provide uniform distribution.
  - Equipped with interchangeable nozzles of different sizes for various applications.
  - Inner rotating system supported by stainless steel ball bearing to guarantee no strain and no oxidation due to humidity.

- ### Applications :
- Sports Fields, Golf Courses
  - Dust Suppression, Green Pastures



### Performance Data

Nozzle (mm)	Pressure (kg/cm <sup>2</sup> )	Radius (mtr)	Discharge (ltr/min)	Irrigated Area (mtr <sup>2</sup> )	Precipitation Rate (mm/h)
26	3.0	42	800	5538	7.0
	4.0	47	926	6939	6.9
	5.0	51	1036	8167	6.8
	6.0	54	1135	9156	6.8
28	3.0	45	917	6361	8.6
	4.0	49	1061	7539	8.4
	5.0	52	1186	8494	8.3
	6.0	55	1300	9498	8.2
≈ 30	4.0	50	1207	7853	9.2
	5.0	54	1350	9156	8.8
	6.0	57	1479	10200	8.7
	7.0	61	1594	11683	9.6
32	4.0	52	1361	8494	9.6
	5.0	56	1522	9847	9.3
	6.0	59	1668	10930	9.1
	7.0	62	1798	12070	8.9
34	5.0	57	1708	10200	10.0
	6.0	61	1872	11683	9.6
	7.0	64	2018	12860	9.4
	8.0	67	2162	14095	9.2

\* Performance is based on ideal conditions of Temperature, Wind Velocity and Humidity.  
 ≈ Standard Nozzle Size

Manufactured as per ISO-7749-1&2 specifications



E-mail: [contactus@automatworld.com](mailto:contactus@automatworld.com)  
 Website: [www.automatworld.com](http://www.automatworld.com)

*Creating a Green World*