

SKIPPER

HT- 43G (1½" Water Gun)



Features

- Available in 1½" BSP/NPT Female Thread Connection
- Both Part Circle & Full Circle adjustments
- Adjustable Jet breaker to provide uniform distribution
- Equipped with interchangeable nozzles of different sizes for various applications
- Inner rotating system supported by stainless steel ball bearing to guarantee no strain and no oxidation due to humidity

- Applications :**
- Sports Fields, Golf Courses
 - Dust Suppression, Green Pastures

Performance Data

Nozzle (mm)	Pressure (kg/cm ²)	Radius (mtr)	Discharge (ltr/min)	Irrigated Area (mtr ²)	Precipitation Rate (mm/h)
12x6	2.0	22	159	1519	6.2
	3.0	25	194	1962	5.9
	4.0	28	224	2461	5.4
	5.0	31	252	3017	5.0
14x6	2.0	24	195	1808	8.5
	3.0	27	251	1289	6.5
	4.0	30	290	2826	6.2
	5.0	33	324	3419	5.7
⚡ 16x6	2.0	26	2857	2123	7.2
	3.0	29	315	2640	7.1
	4.0	32	364	2217	6.8
	5.0	35	406	3846	6.3
18x6	2.0	28	318	2641	7.7
	3.0	31	404	3017	8.0
	4.0	34	471	3629	7.8
	5.0	37	521	4298	7.3
20x6	2.0	30	354	2826	7.5
	3.0	33	490	3419	8.6
	4.0	37	571	4298	8.0
	5.0	41	617	5278	7.0

* Performance is based on ideal conditions of Temperature, Wind Velocity and Humidity.
 ⚡ Standard Nozzle Size

Manufactured as per ISO-7749-1&2 specifications



E-mail: contactus@automatworld.com
 Website: www.automatworld.com

Creating a Green World