

AQ-206PC

Flow Regulating Micro Sprinkler



Applications

- For Uniform irrigation of orchard, vineyards, nursery & under tree where undulating terrain and long lateral lengths are challenging.

Features & Specifications


- Constant flow between range of operating Pressure. 20,28,39,50,62,72,95 and 145LPH : 1.5 ~ 4.0 kg/cm²
- Two Stage wetted diameter control
- Insect proof design
- Specially designed Circlip to easily open micro sprinkler for cleaning by the end user.
- Excellent distribution uniformity.
- Quick thread & push fit adaptor connection
- 4x7mm PE/PVC tube.
- UV & Chemical Resistant material.

Performance Chart


Nozzle Color	Nozzle Size (mm)	Flow Rate (LPH)	Swivel Color (Grey)		Swivel Color (Black)	
			Short Diameter		Large Diameter	
			Diameter (mtr.)		Diameter (mtr.)	
			1 st Stage	2 nd Stage	1 st Stage	2 nd Stage
Purple	0.8mm	20	1.2	3.5	1.6	4.5
Brown	0.9mm	28	1.2	4.0	1.6	5.0
Green	1.1mm	39	1.4	4.0	2.0	6.0
Blue	1.3mm	50	1.6	4.5	2.0	6.5
Yellow	1.4mm	62	1.6	4.6	2.0	7.0
Orange	1.5mm	72	1.8	5.0	2.0	7.2
White	1.8mm	95	2.0	5.5	2.2	7.5
Red	2.0mm	145	2.2	9.6

*Tested at 25cm high above ground

Available Connections




Flow Rate Vs Pressure



Assembly/Exploded View

Parts	Parts Description
1	Body
2	Swivel Grey
3	Circlip
4	Nozzle
5	Nozzle Regulator
6	Diaphragm
7	Adopter
8	Trunk Protector (optional)



AUTOMAT IRRIGATION PRIVATE LIMITED

Website: www.automatworld.com | e-mail: contactus@automatworld.com



<https://www.facebook.com/automatindustries>



<https://www.youtube.com/automatindustries>